


SIGMA-TDHD™









Heavy-Duty Tank Drop Hose

High quality gasoline tank drop hose that is lightweight and flexible with a high abrasion resistant helix for easy drag and handling. Flexible, even in sub-zero temperatures. It's suitable for the transfer of gasoline, ethanol blends (up to E15) and other petroleum products with an aromatic content of 40% or less.



TECHNICAL DATA

Construction	Black, specially compounded NBR/PVC (Up to 40% Aromatics) – static dissipating with a Rigid, orange, right-handed PVC helix with spiraled synthetic yarn	
Safety Factor	4:1	
Temperature	-40°F to +150°F (service temperature depends on actual application)	
Grounding	Embedded tin coated copper wire	
Branding	TEXCEL® SIGMA -TDHD - HEAVY DUTY TANK DROP HOSE -<ID>-LOT	
Compared To	120LT	
Sleeves	SIGMA-TDHD™-Sleeves (flexible PVC banding sleeves) or SIGMA-COIL™ (banding coils) are recommended to accurately follow assembly procedures	
Features	Compatible with gasoline and ethanol blends up to E15	

							
I.D.	Part Number	O.D.	Std. Length	Working Pressure (psi)	Vacuum (in./HG)	Bend Radius	Lbs./Ft.
2"	SPVC-TDHD-2.0	2.63"	20'/60'/100'	65	29	5"	1.12
3"	SPVC-TDHD-3.0	3.81"	20'/60'/100'	65	29	6"	1.38
4"	SPVC-TDHD-4.0	4.72"	20'/60'/100'	65	29	8"	2.19