



CAUTION

Hose fabrications should be performed only by experienced personnel. Static wire must be properly embedded, grounded and tested prior to use to assure grounding of hose and hose assembly.

SIGMA-TD 150™

150psi Heavy-Duty Tank Drop Hose

This lightweight drop hose is designed for higher working pressure applications where 150psi is desired. It's suitable for the transfer of gasoline, ethanol blends (up to E15), and other petroleum products with an aromatic content of 40% or less in both drop and pump off service applications. Its rugged and abrasion-resistant construction allows for a low coefficient of friction for ease and maneuverability.



TECHNICAL DATA

Construction	Black, specially compounded NBR/PVC (up to 60% aromatics) – static-dissipating with a rigid PVC right-handed helix (red) and spiraled synthetic yarn	
Safety Factor	4:1	
Temperature	-40°F to +150°F (service temperature depends on actual application)	
Grounding	Embedded tin coated copper wire	
Branding	TEXCEL® SIGMA-TD150™ - HEAVY DUTY TANK DROP HOSE 150 PSI W.P. -<ID>-LOT	
Compared To	SP353	
Sleeves	SIGMA-TD150™ Sleeves (flexible PVC banding sleeves) or SIGMA-COIL™ (banding coils) are recommended to accurately follow assembly procedures	
Features	Designed for use at a higher 150psi working pressure	

	#						
I.D.	Part Number	O.D.	Std. Length	Working Pressure (psi)	Vacuum (in./HG)	Bend Radius	Lbs./Ft.
2"	SPVC-TD150-2.0	2.73"	20'/60'/100'	150	29	6"	1.26
3"	SPVC-TD150-3.0	3.75"	20'/60'/100'	150	29	7"	1.55
4"	SPVC-TD150-4.0	4.88"	20'/60'/100'	150	29	9"	2.49